



ANACONDA ATEX CABLE-HOSE-FITTINGS for Sealtite®


For unarmoured cables, ATEX certified  I M2 - Ex d I / Ex e I and  II GD - Ex d IIC / Ex e II.



ISO, Explosionproof ATEX cable-hose-fitting, IP 66 / IP 68, nickel-plated brass.




ISO thread	M16x1,5	M16x1,5	M20x1,5	M20x1,5	M20x1,5	M20x1,5	M25x1,5	M25x1,5	M25x1,5	
For Sealtite	inch	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"
Cable min-max	mm	4-7	7-10	7-10	5,5-8	8-10,5	10,5-13	10,5-13	13-15,5	15,5-18
Dimensions in mm	A	71	71	71	74	74	74	75	75	75
	B	15	15	15	15	15	15	15	15	15
	C	26	26	26	30	30	30	35	35	35
	E	25	25	25	32	32	32	36	36	36
	F	24	24	24	30	30	30	35	35	35
Standard pack.	pcs.	10	10	10	10	10	10	10	10	10
Article no. standard		822.010.0	822.011.0	822.009.0	822.012.0	822.013.0	822.014.0	822.015.0	822.018.0	822.019.0
Art. no. high temp.		822.010.3*	822.011.3*	822.009.3*	822.012.3	822.013.3	822.014.3	822.015.3	822.018.3	822.019.3



ISO, Explosionproof ATEX cable-hose-fitting, IP 66 / IP 68, nickel-plated brass.




ISO thread	M32x1,5	M32x1,5	M32x1,5	M40x1,5	M40x1,5	M40x1,5	-	-	-	
For Sealtite	inch	1"	1"	1"	1.1/4"	1.1/4"	1.1/4"	-	-	-
Cable min-max	mm	15-18	18-21	21-23,5	21-24	24-27	27-30	-	-	-
Dimensions in mm	A	90	90	90	94	94	94	-	-	-
	B	15	15	15	15	15	15	-	-	-
	C	45	45	45	54	54	54	-	-	-
	E	45	45	45	55	55	55	-	-	-
	F	42	42	42	48	48	48	-	-	-
Standard pack.	pcs.	10	10	10	10	10	10	-	-	-
Article no. standard		822.023.0	822.024.0	822.025.0	822.029.0	822.030.0	822.031.0	-	-	-
Art. no. high temp.		822.023.3	822.024.3	822.025.3	822.029.3	822.030.3	822.031.3	-	-	-



NPT, Explosionproof ATEX cable-hose-fitting, IP 66 / IP 68, nickel-plated brass.



NPT thread	1/2"	1/2"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	-	
For Sealtite	inch	3/8"	3/8"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	-
Cable min-max	mm	4-7	7-10	5,5-8	8-10,5	10,5-13	10,5-13	13-15,5	15,5-18	-
Dimensions in mm	A	74	74	77	77	77	78	78	78	-
	B	18	18	18	18	18	18	18	18	-
	C	26	26	30	30	30	35	35	35	-
	E	25	25	32	32	32	36	36	36	-
	F	24	24	30	30	30	35	35	35	-
Standard pack.	pcs.	10	10	10	10	10	10	10	10	-
Article no. standard		824.010.0	824.011.0	824.012.0	824.013.0	824.014.0	824.015.0	824.018.0	824.019.0	-
Art. no. high temp.		824.010.3*	824.011.3*	824.012.3	824.013.3	824.014.3	824.015.3	824.018.3	824.019.3	-



ANACONDA ATEX fittings for Sealtite

The ATEX cable-hose-fittings with standard internal EPDM rubber seal have a temperature range of -40°C till +100°C.



The high temperature versions, with a special internal Silicone seal, have a temperature range from -70°C till +220°C.

To obtain IP 68 an additional flat seal between body and enclosure is needed (to be ordered separately).

The nickel-plated brass Anaconda ATEX fittings in ISO are limited on stock; for stainless steel or larger sizes the delivery time will be 6 till 8 weeks.


* In size 3/8" a different clamping range is applicable for the high temperature version (with silicone seal): 6 - 8 mm instead of 4 - 7 mm, respectively 8 - 10 mm instead of 7 - 10 mm.

ANACONDA ATEX CABLE-HOSE-FITTINGS for Sealtite®

For unarmoured cables, ATEX certified  I M2 - Ex d I / Ex e I and  II GD - Ex d IIC / Ex e II.




NPT, Explosionproof ATEX cable-hose-fitting, IP 66 / IP 68, nickel-plated brass.



NPT thread		1"	1"	1"	1.1/4"	1.1/4"	1.1/4"	-	-	-
For Sealtite	inch	1"	1"	1"	1.1/4"	1.1/4"	1.1/4"	-	-	-
Cable min-max	mm	15-18	18-21	21-23,5	21-24	24-27	27-30	-	-	-
Dimensions in mm	A	97	97	97	101	101	101	-	-	-
	B	22	22	22	22	22	22	-	-	-
	C	45	45	45	54	54	54	-	-	-
	E	45	45	45	55	55	55	-	-	-
	F	42	42	42	48	48	48	-	-	-
Standard pack.	pcs.	10	10	10	10	10	10	-	-	-
Article no. standard		824.023.0	824.024.0	824.025.0	824.029.0	824.030.0	824.031.0	-	-	-
Art. no. high temp.		824.023.3	824.024.3	824.025.3	824.029.3	824.030.3	824.031.3	-	-	-




ISO, Explosionproof ATEX cable-hose-fitting, IP 66 / IP 68, stainless steel AISI 316.



ISO thread		M16x1,5	M16x1,5	M20x1,5	M20x1,5	M20x1,5	M20x1,5	M25x1,5	M25x1,5	M25x1,5
For Sealtite	inch	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"
Cable min-max	mm	4-7	7-10	7-10	5,5-8	8-10,5	10,5-13	10,5-13	13-15,5	15,5-18
Dimensions in mm	A	71	71	71	74	74	74	75	75	75
	B	15	15	15	15	15	15	15	15	15
	C	26	26	26	30	30	30	35	35	35
	E	25	25	25	32	32	32	36	36	36
	F	24	24	24	30	30	30	36	36	36
Standard pack.	pcs.	10	10	10	10	10	10	10	10	10
Article no. standard		822.010.9	822.011.9	822.009.9	822.012.9	822.013.9	822.014.9	822.015.9	822.018.9	822.019.9
Art. no. high temp.		822.010.6*	822.011.6*	822.009.6*	822.012.6	822.013.6	822.014.6	822.015.6	822.018.6	822.019.6



ISO, Explosionproof ATEX cable-hose-fitting, IP 66 / IP 68, stainless steel AISI 316.



ISO thread		M32x1,5	M32x1,5	M32x1,5	M40x1,5	M40x1,5	M40x1,5	-	-	-
For Sealtite	inch	1"	1"	1"	1.1/4"	1.1/4"	1.1/4"	-	-	-
Cable min-max	mm	15-18	18-21	21-23,5	21-24	24-27	27-30	-	-	-
Dimensions in mm	A	90	90	90	94	94	94	-	-	-
	B	15	15	15	15	15	15	-	-	-
	C	45	45	45	54	54	54	-	-	-
	E	45	45	45	55	55	55	-	-	-
	F	42	42	42	48	48	48	-	-	-
Standard pack.	pcs.	10	10	10	10	10	10	-	-	-
Article no. standard		822.023.9	822.024.9	822.025.9	822.029.9	822.030.9	822.031.9	-	-	-
Art. no. high temp.		822.023.6	822.024.6	822.025.6	822.029.6	822.030.6	822.031.6	-	-	-

ANACONDA ATEX fittings for Sealtite

The ATEX cable-hose-fittings with standard internal EPDM rubber seal have a temperature range of -40°C till +100°C.



The high temperature versions, with a special internal Silicone seal, have a temperature range from -70°C till +220°C.

To obtain IP 68 an additional flat seal between body and enclosure is needed (to be ordered separately).

The nickel-plated brass Anaconda ATEX fittings in ISO are limited on stock; for stainless steel or larger sizes the delivery time will be 6 till 8 weeks.

* In size 3/8" a different clamping range is applicable for the high temperature version (with silicone seal): 6 - 8 mm instead of 4 - 7 mm, respectively 8 - 10 mm instead of 7 - 10 mm.

ANACONDA ATEX CABLE-HOSE-FITTINGS for Sealtite®


For unarmoured cables, ATEX certified  I M2 - Ex d I / Ex e I and  II GD - Ex d IIC / Ex e II.



NPT, Explosionproof ATEX cable-hose-fitting, IP 66 / IP 68, stainless steel AISI 316.




NPT thread		1/2"	1/2"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	-
For Sealtite	inch	3/8"	3/8"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	-
Cable min-max	mm	4-7	7-10	5,5-8	8-10,5	10,5-13	10,5-13	13-15,5	15,5-18	-
Dimensions in mm	A	74	74	77	77	77	78	78	78	-
	B	18	18	18	18	18	18	18	18	-
	C	26	26	30	30	30	35	35	35	-
	E	25	25	32	32	32	36	36	36	-
	F	24	24	30	30	30	36	36	36	-
	Standard pack.	pcs.	10	10	10	10	10	10	10	10
Article no. standard		824.010.9	824.011.9	824.012.9	824.013.9	824.014.9	824.015.9	824.018.9	824.019.9	-
Art. no. high temp.		824.010.6*	824.011.6*	824.012.6	824.013.6	824.014.6	824.015.6	824.018.6	824.019.6	-



NPT, Explosionproof ATEX cable-hose-fitting, IP 66 / IP 68, stainless steel AISI 316.



NPT thread		1"	1"	1"	1.1/4"	1.1/4"	1.1/4"	-	-	-
For Sealtite	inch	1"	1"	1"	1.1/4"	1.1/4"	1.1/4"	-	-	-
Cable min-max	mm	15-18	18-21	21-23,5	21-24	24-27	27-30	-	-	-
Dimensions in mm	A	97	97	97	101	101	101	-	-	-
	B	22	22	22	22	22	22	-	-	-
	C	45	45	45	54	54	54	-	-	-
	E	45	45	45	55	55	55	-	-	-
	F	42	42	42	48	48	48	-	-	-
	Standard pack.	pcs.	10	10	10	10	10	10	-	-
Article no. standard		824.023.9	824.024.9	824.025.9	824.029.9	824.030.9	824.031.9	-	-	-
Art. no. high temp.		824.023.6	824.024.6	824.025.6	824.029.6	824.030.6	824.031.6	-	-	-



ANACONDA ATEX fittings for Sealtite

The ATEX cable-hose-fittings with standard internal EPDM rubber seal have a temperature range of -40°C till +100°C.



The high temperature versions, with a special internal Silicone seal, have a temperature range from -70°C till +220°C.

To obtain IP 68 an additional flat seal between body and enclosure is needed (to be ordered separately).

The nickel-plated brass Anaconda ATEX fittings in ISO are limited on stock; for stainless steel or larger sizes the delivery time will be 6 till 8 weeks.


* In size 3/8" a different clamping range is applicable for the high temperature version (with silicone seal): 6 - 8 mm instead of 4 - 7 mm, respectively 8 - 10 mm instead of 7 - 10 mm.

ANACONDA ATEX EMC-CABLE-HOSE-FITTINGS for Sealtite®

For armoured cables, ATEX certified  I M2 - Ex d I / Ex e I and  II GD - Ex d IIC / Ex e II.




ISO, Explosionproof ATEX EMC-cable-hose-fitting, IP 66 / IP 68, nickel-plated brass.



ISO thread		M16x1,5	M16x1,5	M20x1,5	M20x1,5	M20x1,5	M20x1,5	M25x1,5	M25x1,5	M25x1,5
For Sealtite	inch	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"
Cable min-max	mm	4-7	7-10	7-10	5,5-8	8-10,5	10,5-13	10,5-13	13-15,5	15,5-18
Dimensions in mm	A	71	71	71	74	74	74	75	75	75
	B	15	15	15	15	15	15	15	15	15
	C	26	26	26	30	30	30	35	35	35
	E	25	25	25	32	32	32	36	36	36
	F	24	24	24	30	30	30	35	35	35
Standard pack.	pcs.	10	10	10	10	10	10	10	10	10
Article EMC standard		822.210.0	822.211.0	822.209.0	822.212.0	822.213.0	822.214.0	822.215.0	822.218.0	822.219.0
Art. EMC high temp.		822.210.3*	822.211.3*	822.209.3*	822.212.3	822.213.3	822.214.3	822.215.3	822.218.3	822.219.3




ISO, Explosionproof ATEX EMC-cable-hose-fitting, IP 66 / IP 68, nickel-plated brass.



ISO thread		M32x1,5	M32x1,5	M32x1,5	M40x1,5	M40x1,5	M40x1,5	-	-	-
For Sealtite	inch	1"	1"	1"	1.1/4"	1.1/4"	1.1/4"	-	-	-
Cable min-max	mm	15-18	18-21	21-23,5	21-24	24-27	27-30	-	-	-
Dimensions in mm	A	90	90	90	94	94	94	-	-	-
	B	15	15	15	15	15	15	-	-	-
	C	45	45	45	54	54	54	-	-	-
	E	45	45	45	55	55	55	-	-	-
	F	42	42	42	48	48	48	-	-	-
Standard pack.	pcs.	10	10	10	10	10	10	-	-	-
Article EMC standard		822.223.0	822.224.0	822.225.0	822.229.0	822.230.0	822.231.0	-	-	-
Art. EMC high temp.		822.223.3	822.224.3	822.225.3	822.229.3	822.230.3	822.231.3	-	-	-



NPT, Explosionproof ATEX EMC-cable-hose-fitting, IP 66 / IP 68, nickel-plated brass.



NPT thread		1/2"	1/2"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	-
For Sealtite	inch	3/8"	3/8"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	-
Cable min-max	mm	4-7	7-10	5,5-8	8-10,5	10,5-13	10,5-13	13-15,5	15,5-18	-
Dimensions in mm	A	74	74	77	77	77	78	78	78	-
	B	18	18	18	18	18	18	18	18	-
	C	26	26	30	30	30	35	35	35	-
	E	25	25	32	32	32	36	36	36	-
	F	24	24	30	30	30	35	35	35	-
Standard pack.	pcs.	10	10	10	10	10	10	10	10	-
Article EMC standard		824.210.0	824.211.0	824.212.0	824.213.0	824.214.0	824.215.0	824.218.0	824.219.0	-
Art. EMC high temp.		824.210.3*	824.211.3*	824.212.3	824.213.3	824.214.3	824.215.3	824.218.3	824.219.3	-

ANACONDA ATEX fittings for Sealtite

The ATEX cable-hose-fittings with standard internal EPDM rubber seal have a temperature range of -40°C till +100°C.



The high temperature versions, with a special internal Silicone seal, have a temperature range from -70°C till +220°C.

To obtain IP 68 an additional flat seal between body and enclosure is needed (to be ordered separately).

The nickel-plated brass Anaconda ATEX fittings in ISO are limited on stock; for stainless steel or larger sizes the delivery time will be 6 till 8 weeks.

* In size 3/8" a different clamping range is applicable for the high temperature version (with silicone seal): 6 - 8 mm instead of 4 - 7 mm, respectively 8 - 10 mm instead of 7 - 10 mm.

ANACONDA ATEX EMC-CABLE-HOSE-FITTINGS for Sealtite®


For armoured cables, ATEX certified  I M2 - Ex d I / Ex e I and  II GD - Ex d IIC / Ex e II.



NPT, Explosionproof ATEX EMC-cable-hose-fitting, IP 66 / IP 68, nickel-plated brass.




NPT thread		1"	1"	1"	1.1/4"	1.1/4"	1.1/4"	-	-	-
For Sealtite	inch	1"	1"	1"	1.1/4"	1.1/4"	1.1/4"	-	-	-
Cable min-max	mm	15-18	18-21	21-23,5	21-24	24-27	27-30	-	-	-
Dimensions in mm	A	97	97	97	101	101	101	-	-	-
	B	22	22	22	22	22	22	-	-	-
	C	45	45	45	54	54	54	-	-	-
	E	45	45	45	55	55	55	-	-	-
	F	42	42	42	48	48	48	-	-	-
Standard pack.	pcs.	10	10	10	10	10	10	-	-	-
Article EMC standard		824.223.0	824.224.0	824.225.0	824.229.0	824.230.0	824.231.0	-	-	-
Art. EMC high temp.		824.223.3	824.224.3	824.225.3	824.229.3	824.230.3	824.231.3	-	-	-



ISO, Explosionproof ATEX EMC-cable-hose-fitting, IP 66 / IP 68, stainless steel AISI 316.




ISO thread		M16x1,5	M16x1,5	M20x1,5	M20x1,5	M20x1,5	M20x1,5	M25x1,5	M25x1,5	M25x1,5
For Sealtite	inch	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"
Cable min-max	mm	4-7	7-10	7-10	5,5-8	8-10,5	10,5-13	10,5-13	13-15,5	15,5-18
Dimensions in mm	A	71	71	71	74	74	74	75	75	75
	B	15	15	15	15	15	15	15	15	15
	C	26	26	26	30	30	30	35	35	35
	E	25	25	25	32	32	32	36	36	36
	F	24	24	24	30	30	30	36	36	36
Standard pack.	pcs.	10	10	10	10	10	10	10	10	10
Article EMC standard		822.210.9	822.211.9	822.209.9	822.212.9	822.213.9	822.214.9	822.215.9	822.218.9	822.219.9
Art. EMC high temp.		822.210.6*	822.211.6*	809.209.6*	822.212.6	822.213.6	822.214.6	822.215.6	822.218.6	822.219.6



ISO, Explosionproof ATEX EMC-cable-hose-fitting, IP 66 / IP 68, stainless steel AISI 316.



ISO thread		M32x1,5	M32x1,5	M32x1,5	M40x1,5	M40x1,5	M40x1,5	-	-	-
For Sealtite	inch	1"	1"	1"	1.1/4"	1.1/4"	1.1/4"	-	-	-
Cable min-max	mm	15-18	18-21	21-23,5	21-24	24-27	27-30	-	-	-
Dimensions in mm	A	90	90	90	94	94	94	-	-	-
	B	15	15	15	15	15	15	-	-	-
	C	45	45	45	54	54	54	-	-	-
	E	45	45	45	55	55	55	-	-	-
	F	42	42	42	48	48	48	-	-	-
Standard pack.	pcs.	10	10	10	10	10	10	-	-	-
Article EMC standard		822.223.9	822.224.9	822.225.9	822.229.9	822.230.9	822.231.9	-	-	-
Art. EMC high temp.		822.223.6	822.224.6	822.225.6	822.229.6	822.230.6	822.231.6	-	-	-



ANACONDA ATEX fittings for Sealtite

The ATEX cable-hose-fittings with standard internal EPDM rubber seal have a temperature range of -40°C till +100°C.

The high temperature versions, with a special internal Silicone seal, have a temperature range from -70°C till +220°C.

To obtain IP 68 an additional flat seal between body and enclosure is needed (to be ordered separately).

The nickel-plated brass Anaconda ATEX fittings in ISO are limited on stock; for stainless steel or larger sizes the delivery time will be 6 till 8 weeks.

* In size 3/8" a different clamping range is applicable for the high temperature version (with silicone seal): 6 - 8 mm instead of 4 - 7 mm, respectively 8 - 10 mm instead of 7 - 10 mm.