




ANAMET CABLE-FITTINGS for Sealtite®

For unarmoured cables, ATEX certified  I M2 - Ex d I / Ex e I and  II GD - Ex d IIC / Ex e II.




ISO / PG / NPT, Explosionproof ATEX cable-fitting, IP 66 / IP 68, standard temperature, nickel-plated brass.
(to be used in combination with the regular Anaconda male NPT fittings)



ISO thread	-	M20x1,5	M20x1,5	M20x1,5	M25x1,5	M25x1,5	M25x1,5	M32x1,5	M32x1,5	
PG thread	11	13,5	13,5	13,5	16	16	16	21	21	
NPT thread	-	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	1"	1"	
For NPT fitting	inch	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	1"	1"	
Dimensions in mm	A	63	63	63	63	63	63	77	77	
	B	15	15	15	15	15	15	15	15	
	Hex C	30	30	30	30	35	35	42	42	
Cable min-max	mm	5,5-8	5,5-8	8-10,5	10,5-13	10,5-13	13-15,5	15,5-18	18-21	
Standard pack.	pcs.	10	10	10	10	10	10	10	10	
Article no.	ISO	-	297.812.0	297.813.0	297.814.0	297.815.0	297.818.0	297.819.0	297.823.0	297.824.0
	PG	297.611.0	297.612.0	297.613.0	297.614.0	297.615.0	297.618.0	297.619.0	297.623.0	297.624.0
	NPT*	-	297.912.0	297.913.0	297.914.0	297.915.0	297.918.0	297.919.0	297.923.0	297.924.0



ISO / PG / NPT, Explosionproof ATEX cable-fitting, IP 66 / IP 68, standard temperature, nickel-plated brass.
(to be used in combination with the regular Anaconda male NPT fittings)



ISO thread	M32x1,5	M40x1,5	M40x1,5	M40x1,5	M50x1,5	M50x1,5	M63x1,5	M63x1,5	M63x1,5	
PG thread	21	29	29	29	36	36	48	48	48	
NPT thread	1"	1.1/4"	1.1/4"	1.1/4"	1.1/2"	1.1/2"	2"	2"	2"	
For NPT fitting	inch	1"	1.1/4"	1.1/4"	1.1/4"	1.1/2"	1.1/2"	2"	2"	
Dimensions in mm	A	77	80	80	80	80	80	80	80	
	B	15	15	15	15	15	15	15	15	
	Hex C	42	48	48	48	57	57	67	67	
Cable min-max	mm	21-24	21-24	24-27	27-30	30-33	33-36	36-39	39-42	42-45
Standard pack.	pcs.	10	10	10	10	5	5	5	5	
Article no.	ISO	297.825.0	297.829.0	297.830.0	297.831.0	297.843.0	297.844.0	297.851.0	297.852.0	297.853.0
	PG	297.625.0	297.629.0	297.630.0	297.631.0	297.643.0	297.644.0	297.651.0	297.652.0	297.653.0
	NPT*	297.925.0	297.929.0	297.930.0	297.931.0	297.943.0	297.944.0	297.951.0	-	-

On request also available in stainless steel AISI 316, part number xxx.xxx.9

Explosionproof cable-fittings must be fitted in combination with a regular ANAMET / ANACONDA male NPT fitting and are especially used in situations where an ATEX 45° or 90° solution is needed



ANAMET ATEX fittings for Sealtite

The ATEX cable-fittings with standard internal EPDM rubber seal have a temperature range of -40°C till +100°C.



The high temperature versions, with a special internal Silicone seal, have a temperature range from -70°C till +220°C.

To obtain IP 68 an additional flat seal between body and enclosure is needed (to be ordered separately).

The nickel-plated brass Anamet ATEX fittings in ISO are limited on stock; for stainless steel or larger sizes the delivery time will be 6 till 8 weeks.

* The NPT version is somewhat longer (1 till 9 mm, depending on the size)

ANAMET CABLE-FITTINGS for Sealtite®

For unarmoured cables, ATEX certified  I M2 - Ex d I / Ex e I and  II GD - Ex d IIC / Ex e II.



ISO / PG / NPT, Explosionproof ATEX cable-fitting, IP 66 / IP 68, *high temperature*, nickel-plated brass.
(to be used in combination with the regular Anaconda male NPT fittings)



ISO thread	-	M20x1,5	M20x1,5	M20x1,5	M25x1,5	M25x1,5	M25x1,5	M32x1,5	M32x1,5	
PG thread	11	13,5	13,5	13,5	16	16	16	21	21	
NPT thread	-	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	1"	1"	
For NPT fitting	inch	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	1"	1"	
Dimensions in mm	A	63	63	63	63	63	63	77	77	
	B	15	15	15	15	15	15	15	15	
	Hex C	30	30	30	30	35	35	42	42	
Cable min-max	mm	5,5-8	5,5-8	8-10,5	10,5-13	10,5-13	13-15,5	15,5-18	18-21	
Standard pack.	pcs.	10	10	10	10	10	10	10	10	
Article no.	ISO	-	297.812.1	297.813.1	297.814.1	297.815.1	297.818.1	297.819.1	297.823.1	297.824.1
	PG	297.611.1	297.612.1	297.613.1	297.614.1	297.615.1	297.618.1	297.619.1	297.623.1	297.624.1
	NPT*	-	297.912.1	297.913.1	297.914.1	297.915.1	297.918.1	297.919.1	297.923.1	297.924.1

ISO / PG / NPT, Explosionproof ATEX cable-fitting, IP 66 / IP 68, *high temperature*, nickel-plated brass.
(to be used in combination with the regular Anaconda male NPT fittings)



ISO thread	M32x1,5	M40x1,5	M40x1,5	M40x1,5	M50x1,5	M50x1,5	M63x1,5	M63x1,5	M63x1,5	
PG thread	21	29	29	29	36	36	48	48	48	
NPT thread	1"	1.1/4"	1.1/4"	1.1/4"	1.1/2"	1.1/2"	2"	2"	2"	
For NPT fitting	inch	1"	1.1/4"	1.1/4"	1.1/4"	1.1/2"	1.1/2"	2"	2"	
Dimensions in mm	A	77	80	80	80	80	80	80	80	
	B	15	15	15	15	15	15	15	15	
	Hex C	42	48	48	48	57	57	67	67	
Cable min-max	mm	21-24	21-24	24-27	27-30	30-33	33-36	36-39	39-42	42-45
Standard pack.	pcs.	10	10	10	10	5	5	5	5	
Article no.	ISO	297.825.1	297.829.1	297.830.1	297.831.1	297.843.1	297.844.1	297.851.1	297.852.1	297.853.1
	PG	297.625.1	297.629.1	297.630.1	297.631.1	297.643.1	297.644.1	297.651.1	297.652.1	297.653.1
	NPT*	297.925.1	297.929.1	297.930.1	297.931.1	297.943.1	297.944.1	297.951.1	-	-

On request also available in stainless steel AISI 316, part number xxx.xxx.6

Explosionproof cable-fitting must be fitted in combination with a regular ANAMET / ANACONDA male NPT fittings and are especially used in situations where an ATEX 45° or 90° solution is needed

